



**GENERAL INFO**

**SEDIMENT REMOVAL CARTRIDGE**

**String Wound Cartridges**

The Puretec GW Series wound sediment cartridges are cost-effective solutions for the reduction of sand, silt, rust, dirt and scale particles.

The GW Series are wound in a precise pattern around the core providing greater surface area. The result is a higher dirt-holding capacity and greater efficiency than standard wound cartridges.

**FEATURES & BENEFITS**

- String-wound design reduces fine sediment from a variety of fluids.
- High dirt-holding capacity.
- Large range, options for coarse to sediment.
- Suitable for mains water supply.
- Temperature ratings up to 93.3 °C (200 °F).
- Flow rates up to 160 litres/minute.

## CARTRIDGE SPECIFICATIONS

Size	Ordering Code	Micron Rating	Size	Flow (Lpm)
10"	<b>GW951</b>	0.5	Standard 2.5" X 10"	25
	<b>GW011</b>	1	Standard 2.5" X 10"	26
	<b>GW051</b>	5	Standard 2.5" X 10"	27
	<b>GW101</b>	10	Standard 2.5" X 10"	32
	<b>GW201</b>	20	Standard 2.5" X 10"	38
	<b>GW501</b>	50	Standard 2.5" X 10"	42
20"	<b>GW012</b>	1	Standard 2.5" X 20"	52
	<b>GW052</b>	5	Standard 2.5" X 20"	54
	<b>GW102</b>	10	Standard 2.5" X 20"	64
	<b>GW202</b>	20	Standard 2.5" X 20"	76
	<b>GW502</b>	50	Standard 2.5" X 20"	84
10" LD	<b>GW01LD1</b>	1	Large diameter 4.5" X 10"	75
	<b>GW05LD1</b>	5	Large diameter 4.5" X 10"	76
	<b>GW10LD1</b>	10	Large diameter 4.5" X 10"	79
	<b>GW20LD1</b>	20	Large diameter 4.5" X 10"	82
20" LD	<b>GW01LD2</b>	1	Large diameter 4.5" X 20"	150
	<b>GW05LD2</b>	5	Large diameter 4.5" X 20"	152
	<b>GW10LD2</b>	10	Large diameter 4.5" X 20"	158
	<b>GW20LD2</b>	20	Large diameter 4.5" X 20"	160

*Micron rating is nominal. Protect from freezing.*